

Ethernet system for serial interfaces

4 ports for RS232, RS422, RS485 or 20 mA CL



MSX-E7511

4 serial interfaces

RS232, RS422, RS485, 20 mA Current Loop

128-byte FIFO buffer for each port

16C950 compatible UART

Optical isolation

Onboard evaluation of user data




Integrated
Ethernet
switch




*Operating temperature



ARM[®]9
Technology



Cascadable,
can be synchronised
in the μ s range



On request:
Compare logic for
synchro trigger signal



on request



More information on
www.addi-data.com

Features

- 24 V digital trigger input
- ARM[®]9 32-bit processor
- 64 MB onboard SDRAM for storing data
- Robust standardized metal housing
- Power Save Mode: Reduced power consumption when no acquisition runs

Safety features

- Status LEDs for fast error diagnostics
- Optical isolation • Input filters

Serial interfaces

- 4 serial interfaces
- RS232, RS422, RS485 and TTY (20 mA Current Loop)
- The port modes can be mixed
- The channels are optically isolated from each other

Interfaces

- Fast 24 V trigger input
- Ethernet switch with 2 ports
- Synchronisation/trigger In/Out
- Line in for 24 V supply and cascading


Communication interfaces

- Web server (configuration and monitoring)
- Command server SOAP for transferring commands
- Data server (TCP/IP or UDP socket) for sending acquisition data
- Event server (TCP/IP socket) for sending system events (Diagnostics such as temperature, short-circuits ...)
- Command server Modbus TCP and Modbus (UDP) for sending commands


Synchronisation/time stamp

Time stamp

Several MSX-E systems can be synchronised with one another in the μ s range through a synchro connection. This allows to start a synchronous data acquisition, to generate trigger events and to synchronise the time on several MSX-E systems. Furthermore, the systems have a time stamp that logs the point in time at which the data was acquired by the system.



The combination of synchronisation and time stamp (TS) allows the clear allocation of signals that were captured by several systems.






Onboard programming / stand-alone operation

Development mode

With the Development mode of the MSX-E systems you can customise your measurement, control and regulation applications to fit your requirements. The programs run directly on the MSX-E systems, which has two advantages: external PCs are relieved and you can process data freely according to your requirements. This helps you to improve the efficiency of your processes and to secure your investments.

Flexibility through firmware and software adaptation

Thanks to the flexibility of the MSX-E product range, the MSX-E7511 system can be easily extended via firmware, e. g. to install additional protocols on the serial interfaces.



Fields of application

The MSX-E7511 Ethernet system features 4 serial interfaces. Depending on the version, the interface standards are RS232, RS422, RS485 and TTY (20 mA Current Loop). Any application can be programmed either through a firmware adaptation or using the Development mode.

Data collector

Via the RS485 interface, the Modbus RTU protocol can be used. For example, temperature sensors featuring an integrated Modbus RTU interface can be read and the complete protocol interpretation can be made on the MSX-E7511 system.

It is thus possible to filter the actual user data - in this case temperature data - and to transmit only this data or to store it in a database.

Onboard calculation

As the system can be programmed, it is possible to effect calculations with the different ports.


Example:

Using a radar sensor, the position of an object is to be displayed. The sensors indicate the distance via RS422.

Three sensors are used:

- Sensor 1 as a reference to control whether there is an object or not.
- Sensor 2 and 3 for establishing the position of the object.

On the MSX-E7511 system, the interface data is read and interpreted. The position of the object is obtained through calculation of the values of sensor 2 and 3 (e.g. as x/y value). Sensor 1 is used to validate the result. The MSX-E7511 system transmits then only the position data to the Client.




Self-sufficient unit


Using further systems from the MSX-E product range, the MSX-E7511 system can also be used as a self-sufficient unit.

Example:

Components are acquired via a scanner (RS232). The MSX-E7511 system reads the barcode and sends the corresponding commands for the processing of the components to a MSX-E1516 Ethernet digital I/O system (handling) and a printer (marking).

There is thus no need for an additional PLC or PC.





Specifications

Serial interfaces

Number of ports:	4
Mode:	RS232, RS422, RS485, 20 mA Current Loop (active, passive) with optical isolation
Configuration:	at ordering
Optical isolation:	1000 V
Transmission mode:	Asynchronous, full or half duplex
Addressing:	Automatic
Memory:	128-byte FIFO memory for sender and receiver
Transfer rate:	Programmable up to 115.2 kBaud Any Baud rate up to 1 MBaud on request
Protocol:	5-, 6-, 7- or 8-bit character 1, 1½ or 2 stop bits
Parity:	Even, odd, none, mark, space
Connectors:	4 x 9-pin D-Sub male connector

Voltage supply, Ethernet, Trigger, Synchro

The specifications for the voltage supply, Ethernet, Trigger, Synchronisation and Electromagnetic Compatibility apply to all MSX-E systems. See page 31.

System features

Interface:	Ethernet acc. to specification IEEE802.3
Dimensions:	220 mm x 140 mm x 50 mm
Weight:	620 g
Degree of protection:	IP 65
Current consumption:	150 mA ± 10 % typ. in idle/power save
Operating temperature:	-40 °C to +85 °C

Ordering information

MSX-E7511

Ethernet system for serial interfaces, 4 ports for RS232, RS422, RS485 or 20 mA CL. Incl. technical description, software drivers and ConfigTools.

Versions

MSX-E7511-XXXX

- A:** RS232, optically isolated
- B:** RS422, optically isolated
- C:** RS485, optically isolated
- D:** 20mA CL

Example: MSX-E7511-AACC

Port 1 = RS232, Port 2 = RS232, Port 3 = RS485, Port 4 = RS485

Connection cables

For serial interfaces

Open cable end, 9-pin D-Sub female connector

ST073-RS232 (A): RS232 cable

ST073-RS422 (B): RS422 cable

ST073-RS485 (C): RS485 cable

ST073-CL (D): 20mA CL cable

Voltage supply

CMX-2x: Shielded cable, M12 5-pin female connector/open end, IP 65

CMX-3x: For cascading, shielded cable, M12 5-pin female connector/male connector IP 65

Trigger/Synchro

CMX-4x: Shielded cable, M12 5-pin female connector/open end, IP 65

CMX-5x: For cascading, shielded cable, M12 5-pin female connector/male connector IP 65

Ethernet

CMX-6x: CAT5E cable, M12 D-coded male connector/RJ45 connector

CMX-7x: For cascading, CAT5E cable, 2 x M12 D-coded male connector

Options

S7 Modbus TCP Client Library for S7: Easy use of the Ethernet systems MSX-E with PLCs

MSX-E 5V-Trigger: Level change of the trigger inputs and outputs to 5 V
MX-Rail (please specify when ordering!), **MX-Screw**